

CSS Fundamentals

Emmanuel BRUNO
Université de Toulon, LIS UMR CNRS 7020
emmanuel.bruno@univ-tln.fr

2026-10-05

Table des matières

1 Overview	1	9.4 Example 3: Hiding Elements	8
2 Introduction to CSS	2	9.5 Fluid Layouts	8
2.1 External CSS (styles.css)	2	9.6 Responsive Units	9
2.2 Minimal CSS+HTML Example	2	9.7 Example: Fluid Layout with Percentage Width and Responsive Units	9
3 CSS Syntax	2	10 Hands-on Exercises	9
4 Common Selectors	3	11 Using CSS Frameworks ? Why ?	9
4.1 Element Selector	3	12 Bootstrap	10
4.2 Class Selector	3	12.1 Key Features:	10
4.3 ID Selector	3	12.2 Quickstart with Bootstrap	10
4.4 Attribute Selector	3	12.3 Using Bootstrap Components:	11
4.5 Parent Selector	3	12.4 Creating a Responsive Grid:	11
4.6 Ancestor Selector	3	12.5 Adding Buttons and Forms:	11
5 Styling Text and Elements	4	12.6 Adding More Bootstrap Components : Modals	12
6 The Cascade Mechanism: Introduction ...	4	12.7 Alerts	12
6.1 The Cascade Mechanism: Specificity	4	12.8 Cards	13
6.2 The Cascade Mechanism: Importance	5	12.9 Tooltips	13
6.3 The Cascade Mechanism: Source Order	5		
7 Box Model	5		
8 Layout Techniques: Display Property	5		
8.1 Positioning	6		
8.2 Flexbox	6		
8.3 Flexbox Example	6		
8.4 Grid	7		
9 Responsive Design and Media Queries ...	7		
9.1 Media Queries Syntax	8		
9.2 Media Query Examples	8		
9.3 Example 2: Responsive Layout	8		

1 Overview

• Topics:

- Introduction to CSS
- CSS Syntax and Selectors
- Styling Text and Elements
- Box Model
- Layout Techniques
- Responsive Design
- Hands-on Exercises

2 Introduction to CSS

- **What is CSS?**

- CSS stands for **Cascading Style Sheets**.
- It is used to control the presentation, formatting, and layout of web pages.
- CSS separates content (HTML) from design, making it easier to maintain and update websites.
- It is a set of specifications see. <https://www.w3.org/Style/CSS/specs.en.html>

- **Why is CSS Important?**

- CSS enhances the user experience by allowing developers to create visually appealing and responsive web pages.
- It enables consistent styling across multiple pages, improving the overall look and feel of a website.
- CSS is essential for modern web development, as it allows for the creation of complex layouts and designs.

- **Key Points:**

- **Selectors:** Target HTML elements to apply styles.
- **Properties and Values:** Define the styles to be applied.
- **Cascading:** Styles can be applied from multiple sources, with rules for resolving conflicts.

2.1 External CSS (styles.css)

```
body {  
  font-family: Arial, sans-serif;  
  background-color: #f0f0f0;  
}  
  
p {  
  color: green;  
  font-size: 16px;  
}
```

2.2 Minimal CSS+HTML Example

```
<!DOCTYPE html>  
<html lang="en">  
  <head>  
    <meta charset="UTF-8">  
    <meta name="viewport"  
content="width=device-width,  
initial-scale=1.0">  
    <title>Minimal CSS Example</title>  
    <!-- Link to External CSS -->  
    <link rel="stylesheet"  
href="styles.css">  
    <!-- Inline CSS -->  
    <style>  
      .inline-style {  
        color: blue;  
        font-size: 20px;  
      }  
    </style>  
  </head>  
  <body>  
    <h1 class="inline-style">Hello,  
World!</h1>  
    <p>This is a paragraph styled with  
external CSS.</p>  
  </body>  
</html>
```

3 CSS Syntax

- **CSS Syntax:**

- A CSS rule consists of a selector and a declaration block.
- CSS:

```
selector {  
  property: value;  
}
```

4 Common Selectors

4.1 Element Selector

- **Element Selector:**

- Targets all instances of an element.
- CSS:

```
p { color: blue; }
```

- HTML:

```
<p>This is a paragraph.</p>  
<p>This is another paragraph.</p>
```

4.2 Class Selector

- **Class Selector:**

- Targets elements with a specific class attribute.
- CSS:

```
.classname { color: green; }
```

- HTML:

```
<p class="classname">This  
paragraph has a class.</p>  
<p>This paragraph does not have a  
class.</p>
```

4.3 ID Selector

- **ID Selector:**

- Targets a single element with a specific ID attribute.
- CSS:

```
#idname { color: red; }
```

- HTML:

```
<p id="idname">This paragraph has  
an ID.</p>  
<p>This paragraph does not have  
an ID.</p>
```

4.4 Attribute Selector

- **Attribute Selector:**

- Targets elements with a specific attribute.
- CSS:

```
[type="text"] { color: blue; }
```

- HTML:

```
<input type="text"  
placeholder="Text input">  
<input type="password"  
placeholder="Password input">
```

4.5 Parent Selector

- **Parent Selector:**

- Targets the direct parent of an element.
- CSS:

```
div > p { color: blue; }
```

- HTML:

```
<div>  
  <p>This paragraph is inside a  
  div.</p>  
</div>  
<p>This paragraph is not inside a  
div.</p>
```

4.6 Ancestor Selector

- **Ancestor Selector:**

- Targets an element that is a descendant of another element.

- ▶ CSS:

```
div p { color: blue; }
```

- ▶ HTML:

```
<div>
  <p>This paragraph is inside a
  div.</p>
</div>
<p>This paragraph is not inside a
div.</p>
```

- ▶ `background-position`: Sets the initial position of the background image.

- ▶ CSS:

```
body {
  background-color: lightgray;
  background-image:
url('background.jpg');
  background-repeat: no-repeat;
  background-position: center;
}
```

5 Styling Text and Elements

• Text Properties:

- ▶ `color`: Sets the text color.
- ▶ `font-family`: Sets the font of the text.
- ▶ `font-size`: Sets the size of the text.
- ▶ `font-weight`: Sets the weight (boldness) of the text.
- ▶ `text-align`: Aligns the text (left, right, center, justify).
- ▶ CSS:

```
h1 {
  color: blue;
  font-family: Arial, sans-serif;
  font-size: 24px;
  font-weight: bold;
  text-align: center;
}
```

• Background Properties:

- ▶ `background-color`: Sets the background color.
- ▶ `background-image`: Sets a background image.
- ▶ `background-repeat`: Controls the repetition of the background image.

6 The Cascade Mechanism: Introduction

• What is the Cascade?

- ▶ The cascade is a mechanism that determines which CSS rules are applied when multiple rules target the same element.
- ▶ It resolves conflicts between different CSS rules based on three main factors:
 - **Specificity**: How specific the selector is.
 - **Importance**: Whether the rule is marked as `!important`.
 - **Source Order**: The order in which the rules appear in the stylesheet.

6.1 The Cascade Mechanism: Specificity

• Specificity:

- ▶ Specificity is a measure of how specific a CSS selector is.
- ▶ More specific selectors have higher priority.
- ▶ CSS:

```
/* Less specific */
p { color: blue; }
/* More specific */
.className { color: green; }
```

```
/* Most specific */
#idname { color: red; }
```

- ▶ HTML:

```
<p>This is a paragraph.</p>
<p class="classname">This
paragraph has a class.</p>
<p id="idname">This paragraph has
an ID.</p>
```

6.2 The Cascade Mechanism: Importance

- **Importance:**

- ▶ The `!important` declaration can be used to override other rules.
- ▶ CSS:

```
p { color: blue !important; }
.classname { color: green; }
```

- ▶ HTML:

```
<p class="classname">This
paragraph will be blue due to
the !important declaration.</p>
```

6.3 The Cascade Mechanism: Source Order

- **Source Order:**

- ▶ When specificity and importance are equal, the last defined rule in the source order is applied.
- ▶ CSS:

```
p { color: blue; }
p { color: red; }
/* The paragraph will be red
```

```
because the last rule is applied
*/
```

- ▶ HTML:

```
<p>This paragraph will be red
because the last rule is
applied.</p>
```

7 Box Model

- **Understanding the Box Model:**

- ▶ Every HTML element is considered a box.
- ▶ The box model consists of: content, padding, border, and margin.
- ▶ CSS:

```
.box {
  width: 200px;
  height: 100px;
  padding: 10px;
  border: 1px solid black;
  margin: 20px;
}
```

- **Box Model Properties:**

- ▶ **width and height:** Set the size of the content area.
- ▶ **padding:** Space between the content and the border.
- ▶ **border:** Surrounds the padding (if any) and content.
- ▶ **margin:** Space outside the border.

8 Layout Techniques: Display Property

- **What is a Layout?**

- ▶ A layout is the arrangement of elements on a web page.
- ▶ It determines how content is organized and presented to the user.

- **What is a Layout Technique?**

- ▶ A layout technique is a method used to control the positioning and alignment of elements on a web page.
- ▶ Common layout techniques include using the display property, Flexbox, and CSS Grid.

- **Display Property:**

- ▶ `display: block;`: The element takes up the full width available.
- ▶ `display: inline;`: The element takes up only as much width as necessary.
- ▶ `display: inline-block;`: The element is formatted as an inline element but can have a width and height.
- ▶ CSS:

```
.block { display: block; }  
.inline { display: inline; }  
.inline-block { display: inline-block; }
```

8.1 Positioning

- **What is Positioning?**

- ▶ Positioning is a technique used to control the placement of elements on a web page.
- ▶ It allows you to specify the exact location of an element within its containing element or the viewport.

- **Positioning:**

- ▶ `position: static;`: Default positioning.
- ▶ `position: relative;`: Positioned relative to its normal position.
- ▶ `position: absolute;`: Positioned relative to the nearest positioned ancestor.
- ▶ `position: fixed;`: Positioned relative to the viewport.
- ▶ CSS:

```
.relative { position: relative;  
top: 10px; left: 10px; }  
.absolute { position: absolute;  
top: 20px; left: 20px; }  
.fixed { position: fixed; top:  
30px; left: 30px; }
```

8.2 Flexbox

- **What is Flexbox?**

- ▶ Flexbox, or the Flexible Box Layout, is a layout model designed to provide a more efficient way to lay out, align, and distribute space among items in a container.
- ▶ It is particularly useful for creating responsive layouts and handling dynamic content.

- **Key Concepts:**

- ▶ **Flex Container:** The parent element that holds the flex items. Defined by `display: flex;`.
- ▶ **Flex Items:** The child elements of the flex container.

- **Flex Container Properties:**

- ▶ `flex-direction`: Direction of the flex items (row, column).
- ▶ `justify-content`: Aligns items along the main axis (flex-start, center, space-between).
- ▶ `align-items`: Aligns items along the cross axis (flex-start, center, stretch).

- **Flex Item Properties:**

- ▶ `flex-grow`: How much a flex item will grow relative to the rest.
- ▶ `flex-shrink`: How much a flex item will shrink relative to the rest.
- ▶ `flex-basis`: Initial size of a flex item.

8.3 Flexbox Example

- **CSS:**

```
.container {  
display: flex;
```

```

flex-direction: row;
justify-content: space-between;
align-items: center;
}
.item {
  flex: 1;
  padding: 10px;
  background-color: lightblue;
  margin: 5px;
}

```

- **HTML:**

```

<div class="container">
  <div class="item">Item 1</div>
  <div class="item">Item 2</div>
  <div class="item">Item 3</div>
</div>

```

- **Explanation:**

- ▶ The `.container` class defines a flex container with `display: flex;`
- ▶ `flex-direction: row;` arranges items in a row.
- ▶ `justify-content: space-between;` distributes space between items.
- ▶ `align-items: center;` aligns items along the cross axis.
- ▶ Each `.item` grows to fill available space equally (`flex: 1;`).

8.4 Grid

- **Grid:**

- ▶ A layout model for creating complex, responsive grid-based layouts.
- ▶ CSS:

```

.grid-container {
  display: grid;
  grid-template-columns:
  repeat(3, 1fr);
}

```

```

gap: 10px;
}
.grid-item {
  background-color: lightblue;
  padding: 20px;
  text-align: center;
}

```

- ▶ **HTML:**

```

<div class="grid-container">
  <div class="grid-item">Item 1</div>
  <div class="grid-item">Item 2</div>
  <div class="grid-item">Item 3</div>
</div>

```

9 Responsive Design and Media Queries

- **What is Responsive Design?**

- ▶ Designing websites that adapt to different screen sizes and devices.
- ▶ Ensures a consistent and optimal user experience across various devices.

- **What are Media Queries?**

- ▶ Media queries are a CSS feature that allows you to apply different styles based on the characteristics of the device, such as screen width, height, orientation, and resolution.

- **Benefits of Media Queries:**

- ▶ Allows for a responsive design that adapts to different devices.
- ▶ Improves user experience by providing optimal layouts for various screen sizes.
- ▶ Reduces the need for separate mobile and desktop versions of a website.

9.1 Media Queries Syntax

- Media queries use the `@media` rule followed by a condition and a block of CSS rules.
- Example:

```
@media (max-width: 600px) {  
  body {  
    background-color: lightblue;  
  }  
}
```

- **Common Media Query Conditions:**

- ▶ `max-width`: Applies styles if the viewport width is less than or equal to the specified value.
- ▶ `min-width`: Applies styles if the viewport width is greater than or equal to the specified value.
- ▶ `max-height`: Applies styles if the viewport height is less than or equal to the specified value.
- ▶ `min-height`: Applies styles if the viewport height is greater than or equal to the specified value.
- ▶ `orientation`: Applies styles based on the device orientation (portrait or landscape).

9.2 Media Query Examples

- **Example 1: Changing Background Color**
- ▶ CSS:

```
@media (max-width: 600px) {  
  body {  
    background-color: lightblue;  
  }  
}  
  
@media (min-width: 601px) {  
  body {  
    background-color: white;  
  }  
}
```

- **Explanation:**

- ▶ The first example changes the background color based on the viewport width.

9.3 Example 2: Responsive Layout

- CSS:

```
.container {  
  display: flex;  
  flex-direction: row;  
}  
  
@media (max-width: 600px) {  
  .container {  
    flex-direction: column;  
  }  
}
```

- **Explanation:**

- ▶ The second example changes the flex direction of a container to a column layout on smaller screens.

9.4 Example 3: Hiding Elements

- CSS:

```
.sidebar {  
  display: block;  
}  
  
@media (max-width: 600px) {  
  .sidebar {  
    display: none;  
  }  
}
```

- **Explanation:**

- ▶ The third example hides the sidebar on screens with a width of 600px or less.

9.5 Fluid Layouts

- **What are Fluid Layouts?**

- ▶ Fluid layouts use relative units like percentages for widths and heights to create flexible and responsive designs.

- They adapt to the size of the viewport, ensuring that content scales appropriately on different devices.
- **Percentage Width:**
 - Using percentage values for width allows elements to resize relative to their parent container.
 - Example:

```
.fluid {
  width: 100%; /* Element takes
up 100% of its parent container's
width */
  max-width: 1200px; /* Maximum
width of the element */
  margin: 0 auto; /* Center the
element horizontally */
}
```

9.6 Responsive Units

- **Viewport Width (vw):** 1vw is equal to 1% of the viewport's width.
- **Viewport Height (vh):** 1vh is equal to 1% of the viewport's height.
- **Example:**

```
.responsive {
  width: 50vw; /* Element takes up
50% of the viewport's width */
  height: 50vh; /* Element takes up
50% of the viewport's height */
}
```

9.7 Example: Fluid Layout with Percentage Width and Responsive Units

- CSS:

```
.container {
  width: 80%; /* Element takes up 80%
```

```
of its parent container's width */
  max-width: 1200px; /* Maximum
width of the element */
  margin: 0 auto; /* Center the
element horizontally */
}
.responsive-box {
  width: 50vw; /* Element takes up
50% of the viewport's width */
  height: 50vh; /* Element takes up
50% of the viewport's height */
  background-color: lightblue;
}
```

- HTML:

```
<div class="container">
  <div class="responsive-
box">Responsive Box</div>
</div>
```

10 Hands-on Exercises

Before studying a framework to be more efficient, let's do some exercises to practice CSS fundamentals.

Please go to [CSS Hands-on](#)

11 Using CSS Frameworks ? Why ?

- **Consistency:**
 - Provides a consistent look and feel across different pages and projects.
 - Ensures uniformity in design elements like buttons, forms, and navigation bars.
- **Efficiency:**
 - Saves time by providing pre-designed components and styles.
 - Reduces the need to write custom CSS from scratch.
- **Responsiveness:**

- Built-in responsive design features that adapt to different screen sizes.
- Ensures your website looks good on all devices.
- **Community and Support:**
 - Large community of developers contributing to the framework.
 - Extensive documentation and support resources available.

12 Bootstrap

- **Origin:**
 - Bootstrap was originally developed by Mark Otto and Jacob Thornton at Twitter.
 - It was released as an open-source project in 2011.
 - The framework quickly gained popularity due to its ease of use and comprehensive set of features.
- **Description:**
 - Bootstrap is a powerful front-end framework for faster and easier web development.
 - It includes HTML, CSS, and JavaScript components for creating responsive and mobile-first websites.
 - The framework provides a wide range of pre-designed components and utilities, such as navigation bars, buttons, forms, modals, and more.
 - Bootstrap is highly customizable and can be extended with custom styles and components.
 - It follows a grid-based layout system, making it easy to create complex and responsive layouts.
 - The framework is well-documented and supported by a large community of developers.

12.1 Key Features:

- **Responsive Design:**

- Built-in responsive design features that adapt to different screen sizes.
- Ensures your website looks good on all devices.
- **Pre-designed Components:**
 - A wide range of components like navigation bars, buttons, forms, modals, and more.
 - Saves time by providing ready-to-use elements.
- **Customizable:**
 - Easy to customize and extend with custom styles and components.
 - Allows for a high degree of flexibility in design.
- **Grid System:**
 - A powerful grid system for creating complex and responsive layouts.
 - Simplifies the process of designing multi-column layouts.
- **Cross-browser Compatibility:**
 - Ensures consistent appearance and behavior across different browsers.
 - Reduces the need for browser-specific adjustments.

12.2 Quickstart with Bootstrap

Use update to date version of Bootstrap from Bootstrap Official Website

- **Include Bootstrap via CDN:**
 - Add the following `<link>` and `<script>` tags to the `<head>` section of your HTML file.

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport"
    content="width=device-width,
    initial-scale=1.0">
  <title>Bootstrap Quickstart</
```

```

<title>
  <!-- Bootstrap CSS -->
    <link href="https://cdn.
jsdelivr.net/npm/bootstrap@5.2.
3/dist/css/bootstrap.min.css"
rel="stylesheet"
integrity="sha384-rbsA2VBKQhggwzxH7pPCa.
crossorigin="anonymous">
</head>
<body>
  <!-- Your content here -->

  <!-- Bootstrap JS and dependencies
-->
    <script src="https://cdn.
jsdelivr.net/npm/bootstrap@5.2.3/
dist/js/bootstrap.bundle.min.js"
integrity="sha384-kenU1KFdBIe4zVF0s0GIM
crossorigin="anonymous"></script>

</body>
</html>

```

```

<div class="collapse navbar-
collapse" id="navbarNav">
  <ul class="navbar-nav">
    <li class="nav-item active">
      <a class="nav-
link" href="#">Home <span class="sr-
only">(current)</span></a>
    </li>
    <li class="nav-item">
      <a class="nav-link"
href="#">Features</a>
    </li>
    <li class="nav-item">
      <a class="nav-link"
href="#">Pricing</a>
    </li>
  </ul>
</div>
</nav>

```

12.3 Using Bootstrap Components:

- Use Bootstrap **classes** to style your HTML elements.
- Example: Creating a responsive navigation bar.

```

<nav class="navbar navbar-expand-lg
navbar-light bg-light">
  <a class="navbar-brand"
href="#">Navbar</a>
  <button class="navbar-toggler"
type="button" data-toggle="collapse"
data-target="#navbarNav"
aria-controls="navbarNav" aria-
expanded="false" aria-label="Toggle
navigation">
    <span class="navbar-toggler-
icon"></span>
  </button>

```

12.4 Creating a Responsive Grid:

Use Bootstrap's grid system to create responsive layouts.

```

<div class="container">
  <div class="row">
    <div class="col-md-4">Column 1</
div>
    <div class="col-md-4">Column 2</
div>
    <div class="col-md-4">Column 3</
div>
  </div>
</div>

```

12.5 Adding Buttons and Forms:

Use Bootstrap classes to style buttons and forms.

```

<button type="button" class="btn btn-
primary">Primary Button</button>

```

```

<form>
  <div class="form-group">
    <label
for="exampleInputEmail1">Email
address</label>
    <input type="email" class="form-
control" id="exampleInputEmail1"
aria-describedby="emailHelp">
  </div>
  <div class="form-group">
    <label for="exampleInputPassword1">Passw
label>
    <input
type="password" class="form-control"
id="exampleInputPassword1">
  </div>
  <button type="submit" class="btn
btn-primary">Submit</button>
</form>

```

```

<div class="modal-header">
  <h5 class="modal-title"
id="exampleModalLabel">Modal
title</h5>
  <button
type="button" class="btn-close"
data-bs-dismiss="modal" aria-
label="Close"></button>
</div>
<div class="modal-body">
  This is a Bootstrap modal.
</div>
<div class="modal-footer">
  <button type="button"
class="btn btn-secondary" data-bs-
dismiss="modal">Close</button>
  <button
type="button" class="btn btn-
primary">Save changes</button>
</div>
</div>
</div>
</div>

```

12.6 Adding More Bootstrap Components : Modals

- Use Bootstrap classes to create modals for displaying content in a dialog box.
- Example:

```

<!-- Button trigger modal -->
<button type="button" class="btn
btn-
primary" data-bs-toggle="modal"
data-bs-target="#exampleModal">
  Launch demo modal
</button>

<!-- Modal -->
<div class="modal fade"
id="exampleModal" tabindex="-1"
aria-
labelledby="exampleModalLabel"
aria-hidden="true">
  <div class="modal-dialog">
    <div class="modal-content">

```

12.7 Alerts

- Use Bootstrap classes to create alert messages for feedback.
- Example:

```

<div class="alert alert-success"
role="alert">
  This is a success alert-check it
out!
</div>
<div class="alert alert-danger"
role="alert">
  This is a danger alert-check it
out!
</div>

```

12.8 Cards

- Use Bootstrap classes to create card components for displaying content.
- Example:

```
<div class="card" style="width: 18rem;">
  
  <div class="card-body">
    <h5 class="card-title">Card title</h5>
    <p class="card-text">Some quick example text to build on the card title and make up the bulk of the card's content.</p>
    <a href="#" class="btn btn-primary">Go somewhere</a>
  </div>
</div>
```

12.9 Tooltips

- Use Bootstrap classes to add tooltips to elements for additional information.
- Example:

```
<button type="button" class="btn btn-secondary" data-bs-toggle="tooltip" data-bs-placement="top" title="Tooltip on top">
  Tooltip on top
</button>
<script>
  var tooltipTriggerList = [].slice.call(document.querySelectorAll('[data-bs-toggle="tooltip"]'))
  var tooltipList = tooltipTriggerList.map(function (tooltipTriggerEl) {
    return new bootstrap.Tooltip(tooltipTriggerEl)
  })
</script>
```